



»AUT 30«

The flexible machine with multifunctional infeed

The AUT 30 is the most flexible of the multipurpose dicers. Whether product is loaded by hand, with the integrated lift-tilt mechanism, or by means of conveyor belts, the AUT 30 adapts itself easily to any task with the appropriate infeed configuration. It can process loose or pre-formed products and blocks. Depending on application the machine can be configured to process meats as well.



Product features:

- » Fully sealed product loading chamber with open drainages
- » Sidewall opening, can be adjusted to product size for loading
- » THC system*
- » High-speed hydraulics guarantee minimum loading times
- » Power-pack for products with high cutting resistance*
- » Speed-pack (adjustable blade speed)*
- » Fully automatic lubrication system
- » Computer controlled and touch screen
- » Product window in blade chamber
- » Integrated lift-tilt mechanism (optional)
 - » Two-part grid
 - » Hardened shear edges and product stabilisers
 - » Simple and safe grid fixation

*Accessories



CE All machines fulfil the strictest CE safety and hygiene regulations.

Technical specifications	AUT 30	AUT 30 HE
Output (Depending on product)	Max. 2.800 kg/hr	Max. 2.800 kg/hr
Loading dimension W x H x L	116 x 116 x 535 mm	116 x 116 x 535 mm
Feed motion	1-40 mm	1-40 mm
Power supply	10,0 kW	11,5 kW
Weight	1.300 kg	1.500 kg
L x W x H	2.150 x 1.680 x 1.650 mm	3.300 x 1.680 x 2.700 mm
Cutting grid sizes	4 x 4 mm - 58 x 58 mm	4 x 4 mm - 58 x 58 mm